



UV LAMPS SPECS

Length	Model	Description	Type*	Diameter/Base	UVC Output Watts	UV $\mu\text{W}/\text{cm}^2$ @1m
6"	GML370	Hot Cathode	PL-S9W/TUV	PL-S	2.4	
	GML180	Hot Cathode	G 4T5	T5/mini bi-pin	0.5	5.4
	GML170	Hot Cathode	OZ4T5	T5/mini bi-pin	0.5	5.4
9"	GML195	Hot Cathode	G 6T5	T5/mini bi-pin	1.0	11
	GML190	Hot Cathode	OZ 6T5	T5/mini bi-pin	1.1	11
12"	GML205	Hot Cathode	G 8T5	T5/mini bi-pin	1.6	17
	GML125	Slimline	G12T5½L/BP	T5/mini bi-pin	6.0	66
	GML075	Slimline	G12T5½VH/BP	T5/mini bi-pin	6.0	66
	GML405	High Output	GPH357T5L/HO	Four-pin	8.5	92
14"	AAWHO/14	High Output	Custom	Four-pin	12	106
16"	GML020	Cold Cathode	782 L 10	T5/single-pin	2.0 / 2.8	20 / 28
	GML120	Cold Cathode	782 VH 10	T5/single-pin	2.0 / 2.8	20 / 28
	GML060	Slimline	G10T5½L	T5/single-pin	5.3	55
	GML350	Slimline	G10T5½L-4P	T5/four-pin	5.3	55
	GML070	Slimline	G10T5½VH	T5/single-pin	5.3	55
18"	GML430	High Output	GSL406T5L/HO	Four-pin	10.0	108
	GML210	Hot Cathode	G15T8	T8/medium bi-pin	3.6	38
	GML215	Hot Cathode	G25T8	T8/medium bi-pin	5.0	54
	GML410	High Output	GSL406T5L/HO	Single-pin	10.0	100
22"	AAWHO/22	High Output	GPH550T5/HO/4	Four-pin	18	174
	GML225MBP	High Output	CUSTOM	T5 15mm Bi-pin	18	157
24"	GML435	High Output	GPH610T5L/HO	Four-pin	16.2	175
	GML0224/4PNO	High Output	CUSTOM	15mm Four-pin	20	168
	GML0244PO	High Output	CUSTOM	15mm Four-pin	20	168
27"	GML025	Cold Cathode	782 L 20	T5/single-pin	3.9 / 5.5	35 / 52
	GML290	Cold Cathode	782 VH 20	T5/single-pin	3.9 / 5.5	35 / 52
	GML325	Slimline	GSL591	T5/single-pin		
	GML355	Slimline	S24T5-4P	T5/four-pin		
	GML415	High Output	GSL610T5L/HO	Single-pin	16.2	140
30"	GML030	Cold Cathode	782 L 25½	T5/single-pin	7.3	75
	GML010	Cold Cathode	782 L 30	T5/single-pin	5.2 / 8.3	46 / 73
36"	GML035	Cold Cathode	782 VH 29	T5/mini bi-pin	5.7 / 9.1	50 / 80
	GML040	Cold Cathode	782 H 30	T5/single-pin	5.2 / 8.3	46 / 73
	GML220	Hot Cathode	G30T8	T8/medium bi-pin	8.3	85
	GML005	Slimline	G36T6L	T5/single-pin	13.8	120
	GML100	Slimline	G36T6L-4P	T5/four-pin	12.7	110
	GML090	Slimline	G36T6VH	T5/single-pin	13.8	120
	GML095	Slimline	G37T6VH	T5/single-pin	15.2	124
	GML420	High Output	GSL843T5L/HO	Single-pin	25	195
	GML440	High Output	GSL843T5L/HO/4	Four-pin	25	195
	48"	GML425	High Output	GSL1148T5L/HO	Single-pin	36.1
GML445		High Output	GSL1148T5L/HO/4	Four-pin	36.1	250
64"	GML015	Slimline	G64T5L	T5/single-pin	26.7	190
	GML017	High Output	GXO64T5L H/O	Single-pin	46	370
	GML140	Slimline	G64T5VH	T5/single-pin	26.7	190
	GML270	Slimline	G64T5L-4P	T5/four-pin	26.7	190

*Ozone is negligible unless noted as OZ for high or VH for very high ozone production.

Length reflects nominal length with standard lamp holders adding 2" overall length. Additional lamp lengths and types available by request