

LED system light



Benefits:

- Optimum illumination of the entire enclosure
- Optionally with clip, screw or magnetic attachment
- Equipment to suit every application

Material:

- Plastic
- Aluminium

Colour:

- Enclosure: RAL 7016

Light colour:

- 4000 K (neutral white)

Supply includes:

- Assembly screws

Note:

- Connection accessories should be ordered separately

Model No.		2500.300	2500.310	2500.311	2500.312	2500.313	Page
Output (lumens)		1200	1200	1200	1200	1200	
Length (mm)		437	437	437	437	437	
Motion sensor		■	■	■	■	■	
Rated operating voltage	100 – 240 V AC	■	■	■	■	■	
	24 V DC	–	–	–	–	–	
Protection class	II (all-insulated)	■	■	■	■	■	
	III (SELV)	–	–	–	–	–	
Equipment	Socket	–	D, earthing-pin	UK	F/B	CH	
	90° rotating connector	■	■	■	■	■	
	Adjustable light direction	■	■	■	■	■	
Adjustable light distribution		■	■	■	■	■	
Approvals	UL/cUL	■	–	–	–	–	
	CSA	■	–	–	–	–	
	CCC	■	–	–	–	–	
	ENEC	■	■	■	■	■	
Installation type	Screw-fastening	■	■	■	■	■	
	Clip attachment	■	■	■	■	■	
	Magnetic attachment to surfaces (accessory)	■	–	–	–	–	
Connection options	Infeed	3-pole	3-pole	3-pole	3-pole	3-pole	
	Through-wiring	3-pole	3-pole	3-pole	3-pole	3-pole	
	Door-operated switch (accessory)	–	–	–	–	–	
Mounting options ¹⁾	Enclosures with a 25 mm pitch pattern	Screw fastening/clip	Directly on the profile	Directly on the profile	Directly on the profile	Directly on the profile	Directly on the profile

Accessories

Rail for interior installation AX	see Internet	see Internet	see Internet	see Internet	see Internet	
Mounting bracket	6205.100	6205.100	6205.100	6205.100	6205.100	
Mounting kit magnet	2500.490	–	–	–	–	14
Door-operated switch	–	–	–	–	–	
Door-operated switch, UL	–	–	–	–	–	

Connection accessories

Infeed, 2-pole	–	–	–	–	–	
Infeed, 2-pole, UL	–	–	–	–	–	
Infeed, 3-pole	2500.400	2500.400	2500.400	2500.400	2500.400	7
Infeed, 3-pole, UL	2500.500	–	–	–	–	7
Through-wiring, 2-pole	–	–	–	–	–	
Through-wiring, 2-pole, UL	–	–	–	–	–	
Through-wiring, 3-pole	2500.430	2500.430	2500.430	2500.430	2500.430	7
Through-wiring, 3-pole, UL	2500.530	–	–	–	–	7

¹⁾ The internal mounting rail AX and the mounting bracket are required when installing in compact enclosures AX

LED system light

Model No.	2500.314	2500.320	2500.200	2500.210	2500.211	Page
Output (lumens)	1200	1200	900	900	900	
Length (mm)	437	437	437	437	437	
Motion sensor	■	■	–	–	–	
Rated operating voltage	100 – 240 V AC	100 – 125 V AC	–	■	■	
	24 V DC	–	■	–	–	
Protection class	II (all-insulated)	■	–	■	■	
	III (SELV)	–	■	–	–	
Equipment	Socket	USA / CDN	–	–	D, earthing-pin	GB
	90° rotating connector	■	■	■	■	■
	Adjustable light direction	■	■	–	–	–
	Adjustable light distribution	■	■	■	■	■
Approvals	UL/cUL	■	■	■	–	–
	CSA	■	–	■	–	–
	CCC	–	■	■	–	–
	ENEC	■	–	■	■	■
Installation type	Screw-fastening	■	■	■	■	■
	Clip attachment	■	■	■	■	■
	Magnetic attachment to surfaces (accessory)	–	■	■	–	–
Connection options	Infeed	3-pole	2-pole	3-pole	3-pole	3-pole
	Through-wiring	3-pole	2-pole	3-pole	3-pole	3-pole
	Door-operated switch (accessory)	–	–	■	■	■
Mounting options ¹⁾	Enclosures with a 25 mm pitch pattern					
	Screw fastening/clip	Directly on the profile	Directly on the profile	Directly on the profile	Directly on the profile	Directly on the profile
Accessories						
Rail for interior installation AX	see Internet	see Internet	see Internet	see Internet	see Internet	
Mounting bracket	6205.100	6205.100	6205.100	6205.100	6205.100	
Mounting kit magnet	–	2500.490	2500.490	–	–	14
Door-operated switch	–	–	2500.460	2500.460	2500.460	14
Door-operated switch, UL	–	–	2500.470	–	–	14
Connection accessories						
Infeed, 2-pole	–	–	–	–	–	
Infeed, 2-pole, UL	–	2500.410	–	–	–	7
Infeed, 3-pole	–	–	2500.400	2500.400	2500.400	7
Infeed, 3-pole, UL	2500.500	–	2500.500	–	–	7
Through-wiring, 2-pole	–	–	–	–	–	
Through-wiring, 2-pole, UL	–	2500.440	–	–	–	7
Through-wiring, 3-pole	–	–	2500.430	2500.430	2500.430	7
Through-wiring, 3-pole, UL	2500.530	–	2500.530	–	–	7

¹⁾ The internal mounting rail AX and the mounting bracket are required when installing in compact enclosures AX