



## Features

- Up to 150 hours battery operation time » with rechargeable lipo battery
- Outdoor use » compact splash-proof housings for devices over 500 N
- Overload protection up to 500 % » with rugged aluminium die cast housing
- Optimized for hand-operated measurements » handles exactly in the measurement axis (optional)

## Technical data

		Order No.:			
		FMI-B10B5	FMI-B10C1	FMI-B10C5	FMI-B10K1
Capacity F(nom)*	N	50	100	500	1000
Resolution**	N	0,05	0,1	0,5	1
Temperature coefficient*	%/K	0,02			
Reproducibility*	% F	0,06			
Repeatability*	% F	0,06			
Hysteresis*	% F	0,15			
Creeping (5min)*	% F	0,15			
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor			
Nominal deflection*	mm	0,13	0,25	0,17	0,34
Measuring shaft		M6			
Max. operating force*	% F(nom)	120			
Breaking force*	% F(nom)	500			



Display	Type	5-digit LCD   12mm   Autoreverse
	Refresh time (ms)	1000
Operation modes	Regular	N   kg   lb
	Peak (real-time)	-
	Limits + Statistics	-
Interface	USB	without
	Hirose	without
	Sensor	without
Power supply	Type	internal LiPo battery   operation time 150h
Temperature (operation)*	°C	0 ... 40
Protection code (EN 60529)	Cable not plugged	Housing
Housing	Material	A-Druckguss
	LxWxH (mm)	150 x 82 x 29
	Weight (kg)	0,48
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)

\*) according VDI/VDE/DKD 2638 at 0,2 ...1 x F(nom) \*\*) according DIN 1319-1

## Scope of Supply

Force gauge with hook, flat head, notched head, conical head, VAC universal charger with EC-, UK- and US-wall plug connector, quickstart operation manual, protection case.