

# SOLENOID VALVES

## SERIES CFB

2/2-way - Normally Closed (NC) and Normally Open (NO)

3/2-way - Normally Closed (NC)



- Solenoid valves for air and water
- Great reliability over time, even in heavy working conditions

Series CFB solenoid valves for general purpose are available in the NC and NO version, 2/2 and 3/2-way.

Special versions are available on demand for the protection against the water hammer or with specific treatments for the interception of aggressive fluids.

The valve function is determined by a poppet or by a diaphragm with operation direct or indirect.

Different versions are available according to the nominal diameter and to the threaded ports, as shown in the following tables.

They can thus satisfy various requirements in terms of flow rates and working pressures.

### General Data

TECHNICAL FEATURES	
Function	2/2 NC - 2/2 NO - 3/2 NC
Operation	Direct acting poppet type - servo-assisted with diaphragm
Pneumatic connections	G1/8 ... G2 threads
Orifice diameter	1.4 ... 50 mm
Flow coefficient kv (l/min)	0.14 ... 45
Operating pressure	0 ÷ 0.8 ... 22 bar
Operating temperature	-10 ÷ 90 ... 140 °C
Fluid	Air, water, liquid and gaseous fluids with max viscosity 37 cst (5° E)
Response time	ON <15 ms - OFF <25 ms
Installation	In any position
MATERIALS IN CONTACT WITH THE MEDIUM	
Body	Brass (alimentary or anti-limestone nickel-platings on demand)
Seals	NBR (CFB-A, CFB-E) - FKM (CFB-B, CFB-D) - EPDM (on demand)
Internal parts	Stainless steel - stainless steel and brass (CFB-D1)
ELECTRICAL FEATURES	
Voltage	12 V DC, 24 V DC - 24 V 50 Hz, 110 V 50/60 Hz, 220/230 V 50/60 Hz
Voltage tolerance	±5% (DC) - ±10% (AC)
Power consumption	10 ... 30 W (DC) - 9 ... 29 VA (AC)
Duty cycle	ED 100%
Insulation class	H (180°C)
Electrical connection	Industry standard form B - DIN EN 175 301-803-A
Protection class	IP65 with connector

**Special versions available on demand.**

**It is recommended to use connections with internal diameters bigger than valve orifices, otherwise there may be a performance change.**

## SOLENOID VALVES

## SERIES CFB - CODING EXAMPLES

## Coding example

<b>CFB</b>	<b>-</b>	<b>A</b>	<b>1</b>	<b>3</b>	<b>L</b>	<b>-</b>	<b>R</b>	<b>1</b>	<b>-</b>	<b>B7</b>	<b>E</b>
------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	-----------	----------

<b>CFB</b>	SERIES
<b>A</b>	OPERATION A = indirect B = indirect with linked diaphragm D = direct E = indirect with coil for heavy-duty applications
<b>1</b>	NUMBER OF WAYS - POSITIONS 1 = 2/2-way - NO 2 = 2/2-way - NC 3 = 3/2-way - NC
<b>3</b>	CONNECTIONS 1 = G1/8 2 = G1/4 3 = G3/8 4 = G1/2 5 = G3/4 6 = G1 7 = G1 1/4 8 = G1 1/2 9 = G2
<b>L</b>	ORIFICE DIAMETER A = 1.4 mm B = 2 mm C = 2.5 mm D = 2.8 mm F = 4 mm G = 6 mm J = 8 mm L = 11.5 mm M = 13 mm N = 13.5 mm P = 18 mm R = 26 mm T = 32 mm X = 45 mm Z = 50 mm
<b>R</b>	SEALS MATERIAL R = NBR W = FKM E = EPDM - <i>Available on request</i>
<b>1</b>	BODY MATERIAL 1 = brass
<b>B7</b>	SOLENOID DIMENSION B7 = 22 mm B8 = 30 mm B9 = 36 mm
<b>E</b>	SOLENOID VOLTAGE B = 24 V AC 50 Hz D = 110 V AC 50/60 Hz E = 230 V AC 50/60 Hz 2 = 12 V DC 3 = 24 V DC

## Table for the coupling between solenoids and valves

For solenoids and their connectors see the dedicated section.

- Coil mod. B8... / B9... - DIN EN 175 301-803-A = connector mod. 124-...
- Coil mod. B7... - Industry Standard form B = connector mod. 122-...

Mod.	24V AC 50 Hz	110V AC 50/60 Hz	220/230V AC 50/60 Hz	12V DC	24V DC
<b>Direct acting solenoid valve, 2/2 NC - 2/2 NO - 3/2 NC</b>					
CFB-D21C-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-D21F-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-D22C-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-D22F-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-D22G-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-D23J-*	B9B (29VA)	B9D (29VA)	B9E (29VA)**	not available	B93 (30W)
CFB-D24J-*	B9B (29VA)	B9D (29VA)	B9E (29VA)**	not available	B93 (30W)
CFB-D24M-*	B9B (29VA)	B9D (29VA)	B9E (29VA)**	not available	not available
CFB-D11A-*	B8BK (15VA)	B8DK (15VA)**	B8EK (15VA)**	B82K (19W)	B83K (19W)
CFB-D12D-*	B8BK (15VA)	B8DK (15VA)**	B8EK (15VA)**	B82K (19W)	B83K (19W)
CFB-D13J-*	B8BK (15VA)	B8DK (15VA)**	B8EK (15VA)**	not available	not available
CFB-D31A-*	B8B (15VA)	B8D (15VA)	B8EK (15VA)	B82 (19W)	B83 (19W)
CFB-D31D-*	B8B (15VA)	B8D (15VA)	B8EK (15VA)	B82 (19W)	B83 (19W)
CFB-D32A-*	B8B (15VA)	B8D (15VA)	B8EK (15VA)	B82 (19W)	B83 (19W)
CFB-D32D-*	B8B (15VA)	B8D (15VA)	B8EK (15VA)	B82 (19W)	B83 (19W)
<b>Indirect acting solenoid valve with constrained diaphragm, 2/2 NC</b>					
CFB-B23L-*	B9B (29VA)	B9D (29VA)	B9E (29VA)	not available	B93 (30W)
CFB-B24N-*	B9B (29VA)	B9D (29VA)	B9E (29VA)	not available	B93 (30W)
CFB-B25P-*	B9B (29VA)	B9D (29VA)	B9E (29VA)	not available	B93 (30W)
CFB-B26R-*	B9B (29VA)	B9D (29VA)	B9E (29VA)	not available	B93 (30W)
<b>Indirect acting solenoid valve, 2/2 NC</b>					
CFB-A23L-*	B7B (9VA)*	B7D (9VA)	B7E (9VA)	B72 (10W)	B73 (10W)
CFB-A24N-*	B7B (9VA)*	B7D (9VA)	B7E (9VA)	B72 (10W)	B73 (10W)
CFB-A25P-*	B7B (9VA)*	B7D (9VA)	B7E (9VA)	B72 (10W)	B73 (10W)
CFB-A26R-*	B7B (9VA)*	B7D (9VA)	B7E (9VA)	B72 (10W)	B73 (10W)
CFB-A27T-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A28X-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A29Z-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
<b>Indirect acting solenoid valve, for heavy-duty applications, 2/2 NC</b>					
CFB-E23L-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E24N-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E25P-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E26R-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E27T-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E28X-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-E29Z-*	B8B (15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
<b>Indirect acting solenoid valve, for heavy-duty applications, 2/2 NO</b>					
CFB-A13L-*	B8B(15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A14N-*	B8B(15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A15P-*	B8B(15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A17T-*	B8B(15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A16R-*	B8B(15VA)	B8D (15VA)	B8E (15VA)	B82 (19W)	B83 (19W)
CFB-A18X-*	B9D (29VA)	B8D (29VA)	B8E (29VA)	not available	B93 (30W)
CFB-A19Z-*	B9B (29VA)	B8D (29VA)	B9E (29VA)	not available	B93 (30W)

\* B7B solenoid with nominal bifrequency of 50/60 Hz


\*\* Only to be used with nominal frequency of 50 Hz

## SOLENOID VALVES


## SERIES CFB - DIMENSIONS

## Series CFB solenoid valve - directly operated - 2/2 NC-NO e 3/2 NC


The direct control of these solenoid valves enables them to work with operating pressures which are equal to zero.  
Ports: G1/8 and G1/2.





EV01




EV02




EV45



2/2 NC



2/2 NO



3/2 NC


Mod.	Function	Ports	Ø Orifice (mm)	Kv (m <sup>3</sup> /h)	Pressure min÷max (bar)	A	B	C	F	G	SW	H	I	L	N	M	Symbol
CFB-D21C-W1*	2/2 NC	G1/8	2.5	0.14	0 ÷ 15 [AC / DC]	11	30	73.8	23	41	17	39	41	30	13	14	EV01
CFB-D21F-W1*	2/2 NC	G1/8	4	0.25	0 ÷ 6 [AC / DC]	11	30	73.8	23	41	17	39	41	30	13	14	EV01
CFB-D22C-W1*	2/2 NC	G1/4	2.5	0.14	0 ÷ 15 [AC / DC]	11	30	73.8	23	41	17	39	41	30	13	14	EV01
CFB-D22F-W1*	2/2 NC	G1/4	4	0.25	0 ÷ 6 [AC / DC]	12	31.5	75	26	41	17	39	41	30	13	14	EV01
CFB-D22G-W1*	2/2 NC	G1/4	6	0.6	0 ÷ 2.5 [AC / DC]***	12	31.5	75	26	41	17	39	41	30	13	14	EV01
CFB-D23J-R1*	2/2 NC	G3/8	8	1	0 ÷ 2 [AC] - 0 ÷ 0.8 [DC]	15	45	89	37	55	27	39	47	36	22	22	EV01
CFB-D24J-R1*	2/2 NC	G1/2	8	1	0 ÷ 2 [AC] - 0 ÷ 0.8 [DC]	15	45	89	37	55	27	39	47	36	22	22	EV01
CFB-D24M-R1*	2/2 NC	G1/2	13	2.4	0 ÷ 1 [AC]	15	45	89	37	55	27	39	47	36	22	22	EV01
CFB-D11A-W1*	2/2 NO	G1/8	1.4	0.07	0 ÷ 22 [AC 50Hz / DC]	11	30	75	23	41	17	39	41	30	13	14	EV02
CFB-D12D-W1*	2/2 NO	G1/4	2.8	0.20	0 ÷ 7.5 [AC 50Hz / DC]	11	30	75	23	41	17	39	41	30	13	14	EV02
CFB-D13J-W1*	2/2 NO	G3/8	8	1	0 ÷ 1.5 [AC 50Hz]	15	45	89	37	55	27	39	47	36	22	22	EV02
CFB-D31A-W1*	3/2 NC**	G1/8	1.4	0.06	0 ÷ 14 [AC / DC]	11	30	79.6	23	41	17	39	41	30	13	14	EV45
CFB-D31D-W1*	3/2 NC**	G1/8	2.8	0.14	0 ÷ 5 [AC / DC]	11	30	79.6	23	41	17	39	41	30	13	14	EV45
CFB-D32A-W1*	3/2 NC**	G1/4	1.4	0.06	0 ÷ 14 [AC / DC]	11	30	79.6	23	41	17	39	41	30	13	14	EV45
CFB-D32D-W1*	3/2 NC**	G1/4	2.8	0.14	0 ÷ 5 [AC / DC]	11	30	79.6	23	41	17	39	41	30	13	14	EV45

\* = choose the suitable solenoid according to the TABLE FOR THE COUPLING BETWEEN SOLENOID AND VALVES

\*\* = the performances shown in the table refer to the use with inlet from "2" and outlet from "1".

\*\*\* = 0 ÷ 4 with B9... solenoid


**Series CFB solenoid valve - with linked diaphragm - 2/2 NC**



The diaphragm which is linked to the mobile plunger is a good arrangement between high fluid flow rates and working pressures (zero pressures as well).

Ports: from G3/8 to G1.

The standard diaphragm is supplied in FKM.



Mod.	Function	Ports	Ø Orifice (mm)	Kv (m <sup>3</sup> /h)	Pressure min÷max (bar)	A	B	C	F	G	H	I	L	SW
CFB-B23L-W1-*	2/2 NC	G3/8	11.5	2.1	0 ÷ 15 [AC] - 0 ÷ 8 [DC]	14	55.8	103.2	45	64	28.2	35.8	36	28
CFB-B24N-W1-*	2/2 NC	G1/2	13.5	2.5	0 ÷ 15 [AC] - 0 ÷ 8 [DC]	14	55.8	103.2	45	69	30.7	38.3	36	28
CFB-B25P-W1-*	2/2 NC	G3/4	18	5	0 ÷ 15 [AC] - 0 ÷ 5 [DC]	21	72	119.4	71	93	43.5	49.5	36	42
CFB-B26R-W1-*	2/2 NC	G1	26	8	0 ÷ 15 [AC] - 0 ÷ 5 [DC]	21	72	119.4	71	93	43.5	49.5	36	42

\* = choose the suitable solenoid according to the TABLE FOR THE COUPLING BETWEEN SOLENOID AND VALVES





**SOLENOID VALVES**
**SERIES CFB - DIMENSIONS**
**Series CFB - indirectly operated - 2/2 NC**


The pilot of these indirectly operated solenoid valves controls the diaphragm position through a differential pressure. These valves are therefore particularly suitable for controlling high fluid flow rates and require very low working pressures to operate.

Ports: from G3/8 to G2.

The standard diaphragm is supplied in NBR.


On demand it can be supplied in FKM or EPDM.



Mod.	Function	Ports	Ø Orifice (mm)	Kv (m <sup>3</sup> /h)	Pressure min-max (bar)	A	B	C	F	G	L	SW
CFB-A23L-R1-*	2/2 NC	G3/8	11.5	2.6	0.1 + 15 [ AC / DC ]	12	32.5	78.5	41.9	57	22	24
CFB-A24N-R1-*	2/2 NC	G1/2	13.5	3.5	0.1 + 15 [ AC / DC ]	15	39.7	85.7	45	69	22	30
CFB-A25P-R1-*	2/2 NC	G3/4	18	5.8	0.2 + 15 [ AC / DC ]	18	46.5	91.5	54.4	74	22	34
CFB-A26R-R1-*	2/2 NC	G1	26	9.5	0.2 + 12 [ AC / DC ]	22.5	59.8	104.5	71	93	22	45
CFB-A27T-R1-*	2/2 NC	G1 1/4	32	12.5	0.4 + 12 [ AC 50 Hz / DC ] - 0.4 + 6 [ AC 60 Hz ]	27.5	73.5	130	86.6	111	30	55
CFB-A28X-R1-*	2/2 NC	G1 1/2	45	31	0.4 + 10 [ AC 50 Hz / DC ] - 0.4 + 3.5 [ AC 60 Hz ]	31	85	138.3	110	138	30	62
CFB-A29Z-R1-*	2/2 NC	G2	50	45	0.4 + 10 [ AC 50 Hz / DC ] - 0.4 + 3.5 [ AC 60 Hz ]	37.5	98.8	152	110	145	30	75

\* = choose the suitable solenoid according to the TABLE FOR THE COUPLING BETWEEN SOLENOID AND VALVES

**Series CFB solenoid valve - indirectly op. for heavy-duty applications - 2/2 NC**




These solenoid valves have a solenoid protection system suitable to be used in particularly humid environments and in harsh conditions.

The system consists of two gaskets placed above and below the coil and a lock nut that integrates the upper gasket.

The standard diaphragm valve supplied is in NBR.

On demand it can be supplied in FKM or EPDM.



Mod.	Function	Ports	Ø Orifice (mm)	Kv (m³/h)	Pressure min÷max (bar)	A	B	C	F	G	L	SW
CFB-E23L-R1-*	2/2 NC	G3/8	11.5	2.6	0.1 ÷ 15 [ AC / DC ]	12	32.5	78.5	41.9	57	30	24
CFB-E24N-R1-*	2/2 NC	G1/2	13.5	3.5	0.1 ÷ 15 [ AC / DC ]	15	39.7	85.7	45	69	30	30
CFB-E25P-R1-*	2/2 NC	G3/4	18	5.8	0.2 ÷ 15 [ AC / DC ]	18	46.5	91.5	54.4	74	30	34
CFB-E26R-R1-*	2/2 NC	G1	26	9.5	0.2 ÷ 12 [ AC / DC ]	22.5	59.8	104.5	71	93	30	45
CFB-E27T-R1-*	2/2 NC	G1 1/4	32	12.5	0.4 ÷ 12 [ AC 50 Hz / DC ] - 0.4 ÷ 6 [ AC 60 Hz ]	27.5	73.5	130	86.6	111	30	55
CFB-E28X-R1-*	2/2 NC	G1 1/2	45	31	0.4 ÷ 10 [ AC 50 Hz / DC ] - 0.4 ÷ 3.5 [ AC 60 Hz ]	31	85	138.3	110	138	30	62
CFB-E29Z-R1-*	2/2 NC	G2	50	45	0.4 ÷ 10 [ AC 50 Hz / DC ] - 0.4 ÷ 3.5 [ AC 60 Hz ]	37.5	98.8	152	110	145	30	75





\* = choose the suitable solenoid according to the TABLE FOR THE COUPLING BETWEEN SOLENOID AND VALVES

**SOLENOID VALVES**
**SERIES CFB - DIMENSIONS**
**Series CFB - indirectly operated - 2/2 NO**


The pilot of these indirectly operated solenoid valves controls the diaphragm position through a differential pressure. These valves are therefore particularly suitable for controlling high fluid flow rates and require very low working pressures to operate.

Ports: from G3/8 to G2.

The standard diaphragm is supplied in NBR. On demand it can be supplied in FKM or EPDM.



Mod.	Function	Ports	Ø Orifice (mm)	Kv (m <sup>3</sup> /h)	Pressure min+max (bar)	A	B	C	F	G	L	SW
CFB-E13L-R1-*	2/2 NO	G3/8	11.5	2.6	0.1 + 15 [ AC / DC ]	12	32.5	78.5	41.9	57	22	24
CFB-E14N-R1-*	2/2 NO	G1/2	13.5	3.5	0.1 + 15 [ AC / DC ]	15	39.7	85.7	45	69	22	30
CFB-A15P-R1-*	2/2 NO	G3/4	18	5.8	0.2 + 15 [ AC / DC ]	18	46.5	92.7	54.4	74	22	36
CFB-A16R-R1-*	2/2 NO	G1	26	9.5	0.2 + 12 [ AC / DC ]	22.5	59.8	104.5	71	93	22	45
CFB-A17T-R1-*	2/2 NO	G1 1/4	32	12.5	0.4 + 12 [ AC / DC ]	27.5	73.5	130	86.6	111	30	55
CFB-A18X-R1-*	2/2 NO	G1 1/2	45	31	0.4 + 10 [ AC / DC ]	31	85	138.3	110	138	36	62
CFB-A19Z-R1-*	2/2 NO	G2	50	45	0.4 + 10 [ AC / DC ]	37.5	98.8	152	110	145	36	75

\* = choose the suitable solenoid according to the TABLE FOR THE COUPLING BETWEEN SOLENOID AND VALVES