

Digital I/O Board with Opto-Isolation for PCI PIO-32/32L(PCI)H



* Specifications, color and design of the products are subject to change without notice.

Features

Opto-coupler isolated input (supporting current sink output) and opto-coupler isolated open-collector output (current sink type)
PIO-32/32L(PCI)H has the 32ch of opto-coupler isolated input (supporting current sink output) and 32ch of opto-coupler isolated open-collector output (current sink type) whose response time is 200μsec. Common terminal provided per 16channels, capable of supporting a different external power supply. Supporting driver voltages of 12 - 24 VDC for I/O.

Opto-coupler bus isolation

As the PCI bus (PC) is isolated from the input and output interfaces by opto-couplers, this product has excellent noise performance.

32 input signals can be used as interrupt request signals

You can use 32 input signals as interrupt request signals and also disable or enable the interrupt in bit units and select the edge of the input signals, at which to generate an interrupt.

Windows/Linux support device driver

Using the device driver API-TOOL makes it possible to create applications of Windows/Linux. In addition, a diagnostic program by which the operations of hardware can be checked is provided.

Equipped with digital filter to prevent wrong recognition of input signals from carrying noise or a chattering

This product has a digital filter to prevent wrong recognition of input signals from carrying noise or a chattering. All input terminals can be added a digital filter, and the setting can be performed by software.

Zener diode for surge voltage protection and the circuit for overcurrent protection

Zener diodes are connected to the output circuits to protect against surge voltages. In addition, the output circuit, it attaches the overcurrent protection circuit at the output 8-channel unit. The output rating is max. 35VDC, 100mA per channel.

Included Items

Product [PIO-32/32L(PCI)H] ... 1

Please read the following ... 1

This product is a PCI bus-compliant interface board for input/output of digital signals. This product can input and output digital signals at 12 - 24VDC.

PIO-32/32L(PCI)H features 32 opto-coupler isolated inputs (supporting current sink output) and 32 opto-coupler isolated open-collector outputs (current sink type). You can use 32 input signals as interrupt inputs. In addition, the digital filter function to prevent wrong recognition of input signals is provided and output transistor protection circuit (surge voltage protection and overcurrent protection).

Windows/Linux device driver is supported with this product.

*The contents in this document are subject to change without notice.

*Visit the CONTEC website to check the latest details in the document.

*The information in the data sheets is as of July, 2023.

Hardware specifications

Function Specifications

Item		Specifications
Input	Type	Opto-Isolated Input (for current sinking output) (Negative logic *1)
	Number of Channels	32ch (all available for interrupts) (One common power supply per 16 channels)
	Input resistance	4.7kΩ
	Current required to turn ON	2.0mA or more
	Current required to turn OFF	0.16mA or less
	Interrupts	Combine 32 interrupt signals to one interrupt request signal as the INTA. Either rising edge or falling edge of input signal can generate interrupt.
	Response time	200μsec within
Output	Type	Opto-Isolated Open Collector Output (current sinking type) (Negative logic *1)
	Number of Channels	32ch (One common power supply per 16 channels)
	Output rated voltage	35VDC (Max.)
	Output rated current	100mA/channel (Max.)
	Residual voltage with output on	0.5V or less (Output current ≤ 50mA), 1.0V or less (Output current ≤ 100mA)
	Surge protector	Zener diode RD47FM(Renesas) or equivalent
	Response time	200μsec within
Common	Connecting distance	50m(Typ.)(depending on wiring environment)
	I/O address	Any 32-byte boundary
	Interruption level	1 level use
	Boards in one system	Maximum of 16 boards can be install in a same system.
	Isolated voltage	500Vrms
	External circuit power supply	12 - 24VDC(±10%)
	Power consumption	5VDC 250mA (Max.)
	PCI bus specification	32bit, 33MHz, Universal key shapes supported *2
	Dimension (mm)	176.4(L) x 106.68(H) *3
	Weight	215g

*1 Data "0" and "1" correspond to the High and Low levels, respectively.


*2 This product requires power supply at +5 V from an expansion slot (it does not work on a machine with a +3.3-V power supply alone).

*3 The size of board No.7212, No.7212A, and No.7212B is 176.4(L) x 105.68 (H) mm.

Installation Environment Requirements


Item	Specifications
Operating ambient temperature	0 - +50°C
Operating ambient humidity	10 - 90%RH (No condensation)
Floating dust particles	Not to be excessive
Corrosive gases	None
Standard	VCCI Class A, CE Marking (EMC Directive Class A, RoHS Directive), UKCA

Physical Dimensions



The standard outside dimension (L) is the distance from the end of the board to the outer surface of the slot cover.

For substrate No. 7212, 7212A, 7212B, 7212C



The standard outside dimension (L) is the distance from the end of the board to the outer surface of the slot cover.

Support Software

You can use CONTEC support software according to your purpose and development environment.

For more details on the supported OS, applicable languages, or to download the latest version of software, visit the CONTEC Web site.

Name	Contents	How to get
Windows Version Digital I/O Driver software API-DIO(WDM)	The Windows device driver is provided as a form of Windows API functions. Various sample programs such as C# and Visual Basic .NET, Visual C++, Python etc. and diagnostic program useful for checking operation is provided.	Download from the CONTEC website *1
Linux Version Digital I/O Driver software API-DIO(LNX)	The Linux device driver is provided as a shared library. The software includes various sample programs such as gcc (C, C++) and Python programs, as well as a configuration tool to configure the device settings.	Download from the CONTEC website *1
Software Development Tool Kits (SDK) and Support Software	In addition to the device drivers, we offer many software programs for using CONTEC devices in an easier manner.	Download from the CONTEC website *2

*1 Download the files from the following URL.
<https://www.contec.com/download/>

*2 For supported software, search the CONTEC website for this product and view the product page.
<https://www.contec.com/>

Optional Products

Product Name	Model type	Description
Shield Cable with 96-Pin Half-Pitch Connector at Both Ends (Mold Type)	PCB96PS-0.5P	0.5m
	PCB96PS-1.5P	1.5m
	PCB96PS-3P	3m
	PCB96PS-5P	5m
	PCB96P-1.5	1.5m
Flat Cable with 96-Pin Half-Pitch Connectors at Both Ends	PCB96P-1.5	1.5m
	PCB96P-3	3m
	PCA96PS-0.5P	0.5m
	PCA96PS-1.5P	1.5m
Shield Cable with 96-Pin Half-Pitch Connector at One End (Mold Type)	PCA96PS-1.5P	1.5m
	PCA96PS-3P	3m
	PCA96PS-5P	5m
	PCA96P-1.5	1.5m
Flat Cable with 96-Pin Half-Pitch Connector at One End	PCA96P-1.5	1.5m
	PCA96P-3	3m
	PCA96P-5	5m
Distribution Shield Cable with 96-Pin Half-Pitch Connector (96Pin→37Pin x 2)	PCB96WS-1.5P	1.5m
	PCB96WS-3P	3m
	PCB96WS-5P	5m
Screw Terminal Unit (M3 x 96P)	EPD-96A	*1 *2
Screw Terminal Unit (M3.5 x 96P)	EPD-96	*2
Screw Terminal Unit (M3 x 37P)	EPD-37A	*1 *3
Screw Terminal Unit (M3.5 x 37P)	EPD-37	*3
Digital I/O 64CH Series Terminal Panel (M3 x 96P)	DTP-64A	*2
Termination Panel (M3)	DTP-3C	*3
Termination Panel (M2.5)	DTP-4C	*3
Signal Monitor for Digital I/O (64bit)	CM-64L	*2
Signal Monitor for Digital I/O (32bit)	CM-32L	*3
Connection Conversion Board (96P→37P x 2)	CCB-96	*4

*1 "Spring-up" type terminal is used to prevent terminal screws from falling off.


*2 PCB96P or PCB96PS optional cable is required separately.

*3 PCB96WS optional cable is required separately.

*4 "Spring-up" type terminal is used to prevent terminal screws from falling off.

Visit the CONTEC website for the latest optional products.

Component Name




No.	Name
1	Interface Connector
2	Board ID Setting Switch

CAUTION

The product doesn't have the built-in power setting function.

Connecting an Interface Connector

To connect an external device to this product, plug the cable from the device into the interface connector (CN1) shown below.



Layout on the Interface Connector(CN1)

Common plus pin for +6/+7 output ports	OP-6/7 B48	A48	IP-2/3	Common plus pin for +2/+3 input ports
	OP-6/7 B47	A47	IP-2/3	
+7 port (output)	O-77 B46	A46	I-37*	+3 port (input)
	O-76 B45	A45	I-36*	
	O-75 B44	A44	I-35*	
	O-74 B43	A43	I-34*	
	O-73 B42	A42	I-33*	
	O-72 B41	A41	I-32*	
	O-71 B40	A40	I-31*	
	O-70 B39	A39	I-30*	
	O-67 B38	A38	I-27*	
	O-66 B37	A37	I-26*	
+6 port (output)	O-65 B36	A36	I-25*	+2 port (input)
	O-64 B35	A35	I-24*	
	O-63 B34	A34	I-23*	
	O-62 B33	A33	I-22*	
	O-61 B32	A32	I-21*	
	O-60 B31	A31	I-20*	
	O-60 B31	A31	I-20*	
Common minus pin for +6/+7 output ports	ON-6/7 B30	A30	N.C.	N.C.
	ON-6/7 B29	A29	N.C.	
	N.C. B28	A28	N.C.	
	N.C. B27	A27	N.C.	
	N.C. B26	A26	N.C.	
	N.C. B25	A25	N.C.	
	N.C. B24	A24	N.C.	
	N.C. B23	A23	N.C.	
	N.C. B22	A22	N.C.	
	N.C. B21	A21	N.C.	
Common plus pin for +4/+5 output ports	OP-4/5 B20	A20	IP-0/1	Common plus pin for +0/+1 input ports
	OP-4/5 B19	A19	IP-0/1	
	O-57 B18	A18	I-17*	
	O-56 B17	A17	I-16*	
	O-55 B16	A16	I-15*	
	O-54 B15	A15	I-14*	
	O-53 B14	A14	I-13*	
	O-52 B13	A13	I-12*	
	O-51 B12	A12	I-11*	
	O-50 B11	A11	I-10*	
+5 port (output)	O-57 B18	A18	I-17*	+1 port (input)
	O-56 B17	A17	I-16*	
	O-55 B16	A16	I-15*	
	O-54 B15	A15	I-14*	
	O-53 B14	A14	I-13*	
	O-52 B13	A13	I-12*	
	O-51 B12	A12	I-11*	
	O-50 B11	A11	I-10*	
	O-50 B11	A11	I-10*	
	O-50 B11	A11	I-10*	

+4 port (output)	O-47	B10	+0 port (input)	A10	I-07*
	O-46	B09		A09	I-06*
	O-45	B08		A08	I-05*
	O-44	B07		A07	I-04*
	O-43	B06		A06	I-03*
	O-42	B05		A05	I-02*
	O-41	B04		A04	I-01*
	O-40	B03		A03	I-00*
Common minus pin for +4/+5 output ports	ON-4/5	B02	N.C.	A02	N.C.
	ON-4/5	B01		A01	N.C.

* I-00 - I-37 can be used as interrupt signal.

The numbers in square brackets [] are pin numbers designated by HONDA TSUSHIN KOGYO CO., LTD.

Signal name	Description
I-00 - I-37	32 input signal pins. Connect output signals from the external device to these pins.
O-40 - O-77	32 output signal pins. Connect these pins to the input signal pins of the external device.
IP-0/1	Connect the positive side of the external power supply. These pins are common to 16 input signal pins.
IP-2/3	Connect the positive side of the external power supply. These pins are common to 16 input signal pins.
OP-4/5	Connect the positive side of the external power supply. These pins are common to 16 output signal pins.
OP-6/7	Connect the positive side of the external power supply. These pins are common to 16 output signal pins.
ON-4/5	Connect the negative side of the external power supply. These pins are common to 16 output signal pins.
ON-6/7	Connect the negative side of the external power supply. These pins are common to 16 output signal pins.
N.C.	This pin is left unconnected.

CAUTION


To perform input/output using this product with the CONTEC device driver, specify logical ports and logical bits when calling each function. For details, refer to the "Relationships between API-TOOL Logical Ports/Bits and Connector Signal Pins" of Reference Manual.

Connecting Input and Output Signals

Connect the input signals to a device which can be current-driven, such as a switch or transistor output device.

The connection requires an external power supply to feed currents. The product inputs the ON/OFF state of the current-driven device as a digital value.


Input Circuit



The input circuits of interface blocks of the PIO-32/32L(PCI)H are illustrated in the figure above.

The signal inputs are isolated by opto-couplers (ready to accept current sinking output signals). The product therefore requires an external power supply to drive the inputs. The power requirement for each input pin is about 5.1 mA at 24 VDC (about 2.6 mA at 12 VDC).

Connecting a Switch (An Example to use Input I-00)




When the switch is ON, the corresponding bit contains 1. When the switch is OFF, by contrast, the bit contains 0.

Output Circuit

Connect the output signals to a current-driven controlled device such as a relay or LED.

The connection requires an external power supply to feed currents. The product controls turning on/off the current-driven controlled device using a digital value.



The output circuits of interface blocks of the PIO-32/32L(PCI)H are illustrated in the figure above.

The signal output section is an opto-coupler isolated, open-collector output (current sink type).

The rated output current per channel is 100mA at maximum. The output section can also be connected to a TTL level input as it uses a low-saturated transistor for output.

The residual voltage (low-level voltage) between the collector and emitter with the output on is 0.5V or less at an output current within 50mA or at most 1.0V at an output current within 100mA.


A zener diode is connected to the output transistor for protection from surge voltages.

An overcurrent protection component is provided for every 8 output transistors.

CAUTION

When the PC is turned on, all outputs are reset to OFF.


Connection to the LED (An Example to use Output O-40)



When "1" is output to a relevant bit, the corresponding LED comes on. When "0" is output to the bit, in contrast, the LED goes out.


Example of Connection to TTL Level Input (Connection Example of

Output and TTL level Input Signal)




Connecting the Sink Type Output and Sink Output Support Input

The following example shows a connection between a sink type output (output board) and a sink output support input (input board). Refer to this connection example when you connect such boards to each other.



Block Diagram



Differences between the PIO-32/32L(PCI)H and PIO-32/32L(PCI)

The PIO-32/32L(PCI)H is connector-pin compatible with the conventional PIO-32/32L(PCI) but has the following differences from it :

- (1) Different in the number of input signals available to interrupt requests
 - PIO-32/32L(PCI)H : All of 32 channels
 - PIO-32/32L(PCI) : 4 channels
- (2) Different in the expression to calculate the digital filter time (n: setting value)
 - PIO-32/32L(PCI)H : $2^n / (8 \times 10^6)$
 - PIO-32/32L(PCI) : $2^n / (16 \times 10^6)$
- (3) Protective elements provided for outputs
 - PIO-32/32L(PCI)H : Surge protector: Zener diode
 - PIO-32/32L(PCI) : Nothing
- (4) Different in interrupt level resource allocation
 - PIO-32/32L(PCI)H : Automatically allocates on interrupt level.
 - PIO-32/32L(PCI) : Uses a jumper switch to select whether to allocate interrupt levels.