



CONFIGURATION

| | |
|---------------------------|---|
| L Control | Standard Screw Adjustment |
| A Adjustment Range | 200 - 3000 psi (14 - 210 bar), 1000 psi (70 bar) Standard Setting |
| N Seal Material | Buna-N |

This is a normally closed, balanced poppet, switching element. When pilot pressure is applied to port 3, the poppet remains closed until the pilot pressure reaches the setting established by the integral pilot relief stage, at which point the poppet shifts to the open position.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|-------------------------|
| Cavity | T-23A |
| Series | 3 |
| Capacity | 60 gpm |
| Maximum Operating Pressure | 5000 psi |
| Minimum Pilot Pressure Required to Shift Valve | 300 psi |
| Control Pilot Flow | See Performance Data |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 10 drops/min.@5000 psi |
| Valve Hex Size | 1 1/4 in. |
| Valve Installation Torque | 150 - 160 lbf ft |
| Adjustment Screw Internal Hex Size | 5/32 in. |
| Locknut Hex Size | 9/16 in. |
| Locknut Torque | 80 - 90 lbf in. |
| Seal kit - Cartridge | Buna: 990023007 |
| Seal kit - Cartridge | Polyurethane: 990023002 |
| Seal kit - Cartridge | Viton: 990023006 |
| Model Weight | 1.67 lb. |

CONFIGURATION OPTIONS

Model Code Example: **DKHPLAN**

| CONTROL (L) | ADJUSTMENT RANGE (A) | SEAL MATERIAL (N) |
|---|--|-------------------|
| L Standard Screw Adjustment | A 200 - 3000 psi (14 - 210 bar), 1000 psi (70 bar) Standard Setting | N Buna-N |
| C Tamper Resistant - Factory Set | B 200 - 1500 psi (14 - 105 bar), 1000 psi (70 bar) Standard Setting | V Viton |
| K Handknob | D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting | |
| | W 200 - 4500 psi (14 - 315 bar), 1000 psi (70 bar) Standard Setting | |

TECHNICAL FEATURES

- Unique balanced construction provides predictable switching with 5000 psi (350 bar) at both port 1 and port 2. When the remote pressure signal at port 3 exceeds the internal valve setting, the valve shifts to the open position.
- Any backpressure at the drain port is directly additive to the valve setting.
- Valve will reseal when the pilot pressure falls to 85% of the cracking value.
- Port 1 and port 2 are fully sealed from port 3 and port 4. Ports 3 and 4 are positively sealed.
- Leakage rate between port 1 and port 2 is very low, typically less than 10 drops/min. at 5000 psi (0,7 cc/min at 350 bar).
- All ports will accept 5000 psi (350 bar).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

