

Universal flexible DV wire-clamps in polychloroprene rubber (Neoprene)



HELAVIA®




DV

Material: CR
Colours: black
Operating temperatures: -30 to +90°C
Tensile strength at break: > 8 MPa
Ultimate elongation: > 600 %
Dielectric strength: > 13 kV/mm
Applications: for protection and strain relief, very effective when used with SES-QUICK cable ties, in the passages of boxes, of cupboards or crankcase, etc.



• DV wire-clamps in Bags, without ties

type	article number	dimensions (mm)					pcs	cable ties to be used	
		housing Ø	wire Ø	Ø A	B	C		type	article number
DV 4 / 9	0252 0511 010	16	4 - 9	24	18,6	3	100	145/34 SL-C	0186 0979 010
DV 7 / 12	0252 0521 010	19	7 - 12	28	18,7	3	100	145/34 SL-C	0186 0979 010
DV 12 / 18	0252 0531 010	25	12 - 18	34	22	3	100	185/46 SL-C	0186 0983 010
DV 18 / 25	0252 0541 010	32	18 - 25	43	24	3	50	185/46 SL-C	0186 0983 010
DV 25 / 32	0252 0551 010	38	25 - 32	51	24,5	4	50	185/46 SL-C	0186 0983 010



• DV wire-clamps in Bags, with ties

type	article number	dimensions (mm)					pcs	delivered with ties
		housing Ø	wire Ø	Ø A	B	C		
DV 4 / 9	0252 0510 010	16	4 - 9	24	18,6	3	10	145/34 SL-C
DV 7 / 12	0252 0520 010	19	7 - 12	28	18,7	3	10	145/34 SL-C
DV 12 / 18	0252 0530 010	25	12 - 18	34	22	3	10	185/46 SL-C
DV 18 / 25	0252 0540 010	32	18 - 25	43	24	3	5	185/46 SL-C
DV 25 / 32	0252 0550 010	38	25 - 32	51	24,5	4	5	185/46 SL-C

Assembly instruction

