



AEC028R05ADC2AB342000000200100CD01B

222AK00192B [↗](#)**Where to buy** [↗](#)

Product specifications

Characteristic	Value
Aux mount output shaft	NO AUXILIARY MOUNT
Brand	Danfoss
CODE TITLE	220 SERIES MOBILE PISTON PUMP
Control special features	NO CONTROL SPECIAL FEATURES
Controller type	PCLS WMETRIC LS PORT (LEFT)
Design Code	SECOND DESIGN
Diagnostic pressure ports	M12 X1.5 METRIC O-RING-PLUGGED
Displacement	28.0 CM3R [1.71 IN3R]
Drain port size location	M22 X 1.5 METRIC O-RING-TOP
Flow comp rpc setting	[250-290 lbf/in ²]
Front mounting input shaft	2 BOLT B, .88" DIA SHAFT
Identification packaging	MARK EATON PN AND MODEL CODE
Input shaft rotation	RIGHT HAND ROTATION (CW)
Main ports size location	SP INM42" OUT27" ISO MET
Maximum displacement option	EXT MANUAL ADJ (SET AT MAX)
PRESSURE COMP SETTING	[3400-3500 lbf/in ²]
PUMP SPECIAL FEATURES	NO PUMP SPECIAL FEATURES
Paint	BLUE PRIMER PER SPEC 209-13CD
Secondary comp setting	NO SECONDARY COMP SETTING
Shaft seal	FLUOROCARBON RUBBER SHAFT SEAL

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [↗](#)

