


IMN 70 INOX

MAGNETIC LEVEL SWITCH




General	Operating principle	IMN level magnetic sensors are based on about <i>reed</i> switches inside the tube, which are activated by a magnet hosted inside the float action and moves to the thrust of the liquid.
	Application	<ul style="list-style-type: none"> For the detection of a single point level in liquids. Used in filling, hollowed out manoeuvres alarm of overflow, etc.

Housing	Electrical connection	By hose cable of two conductors.
	Length	1 m. Other lengths on request.
	Cable material (Temperature)	Silicone (130 °C) PVC (70 °C)

Body	Guide tube	SS AISI316 (1.4401). Ø12 mm
	Run float	16 mm
	Temperature	-40..+125 °C
	Mounting position	Vertical, ±15°
	Protection	IP65. Encapsulated with resin epoxy.

Process connection	Thread	1/4" G	
	Material	SS AISI316 (1.4401)	
	E (mm)	2	
	LR (mm)	11	
	LCP (mm)	4	
	e/c (mm)	17	

Floats	Model	FEI601M13
	Material	SS AISI316L (1.4404)
	Dimension (mm)	Ø 52x52
	Pressure (kg/cm ²)	30
	Density (g/cm ³)	e > 0,76
	FS / FH (mm)	12,5 / 39,5



Contacts	Class	120 WVA / 250 VAC-3A
	Type	Reversing the float position, the contact can be NO or NC
	Situation	

Ordering code	IMN 70 INOX
---------------	-------------